

MATERIAL SAFETY DATA SHEET

Company Name: C.R. LAURENCE CO., INC.
Address: 2503 E. VERNON AVE.
City / State / Zip: LOS ANGELES / CA / 90058
US-CHEMTREC Phone(I): (800)424-9300
US-CHEMTREC Phone(II): (703)527-3887
CAN-CANUTEC Phone: (613)996-6666
Vendor Update: 4/6/2005
Date Prepared: 4/6/2005
MSDS Number: N40055GL ; N4005GL ; N400G15 ;

I. CHEMICAL PRODUCT IDENTIFICATION

Product Name: TWO PART POLYSULFIDE SEALANT – PART B
HMIS Ratings:

Health: Moderate(2)
 Flammability: Slight(1)
 Instability/Reactivity: Slight(1)
 Personal Protective Equipment: NONE

NFPA Ratings:

II. COMPOSITION, INFORMATION ON INGREDIENTS

Chemical Ingredients	C.A.S. Number	% By Weight	ACGIH TLV TWA/STEL	OSHA PEL TWA/STEL	Other TWA/STEL	LD50	LC50
MANGANESE DIOXIDE	131-13-9	15 – 17	0.05 MG/M ³				
<i>Notes</i>							
LEAD PEROXIDE	1309-60-0	3.0 – 6.0		50 UG/M ³			
<i>Notes</i>							

III. HAZARDS IDENTIFICATION PRIMARY ROUTE OF ENTRY

Other: LISTED CARCINOGEN, MUTAGEN, TERATOGEN: NONE LISTED.

IV. FIRST AID MEASURES

Eyes: THOROUGHLY FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF REDNESS OR ITCHING DEVELOPS, HAVE EYES EXAMINED AND TREATED.

Skin: FLUSH WITH WATER. REMOVE CONTAMINATED CLOTHING. WASH THOROUGHLY WITH SOAP AND WATER. IF IRRITATION PERSISTS, CALL PHYSICIAN.

Ingestion: DRINK 2 GLASSES WATER. IF GASTROINTESTINAL SYMPTOMS DEVELOP. SEEK MEDICAL ATTENTION.

Inhalation: REMOVE TO FRESH AIR. IF NOT BREATHING GIVE ARTIFICIAL RESPIRATION. IF BREATHING IS LABORED, GIVE OXYGEN AND CALL PHYSICIAN.

V. FIRE FIGHTING MEASURES

Flash Point: >450°F

Lower Flammability Limit: NOT ESTABLISHED

Upper Flammability Limit: NOT ESTABLISHED

Extinguishing Agents: WATER FOG, CARBON DIOXIDE, DRY CHEMICAL, FOAM

Unusual Fire or Explosion Hazards: EXCESSIVELY HEATED MATERIAL MAY LIBERATE TOXIC OR IRRITATING FUMES.
WEAR SELF CONTAINED BREATHING APPARATUS.

VI. ACCIDENTAL RELEASE MEASURES

Containment/Cleanup: ABSORB MATERIAL USING AN INERT ABSORBENT AND RECONTAINERIZE. REMOVE TO WELL VENTILATED AREA AND TREAT WITH DILUTE AMMONIA (8%) AND LIQUID DETERGENT (8%) SOLUTION. USE 10 PARTS OF THIS SOLUTION FOR EACH PART OF THE SPILLED MATERIAL. LET STAND 48 HOURS VENTED.

VII. HANDLING AND STORAGE

Other: STORE BETWEEN 34° AND 120°F.
AVOID WATER OR MOISTURE CONTAMINATION.
FOR SALE TO, USE AND STORAGE BY SERVICE PERSONNEL ONLY.
KEEP OUT OF REACH OF CHILDREN.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: SAFETY GLASSES WITH SHIELDS

Skin: PROTECTIVE GLOVES: RUBBER OR NEOPRENE.
OTHER PROTECTIVE EQUIPMENT: COVERALLS, RUBBER BOOTS

Respiratory: NONE REQUIRED IF TLV IS NOT EXCEEDED

Engineering: LOCAL MECHANICAL

IX. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: BLACK PASTE

Boiling Point: >300°F

Solubility in Water: INSOLUBLE

Specific Gravity: 1.6

Vapor Pressure: NOT ESTABLISHED

Vapor Density: 8.5

Volatile Content: % VOLATILES: NIL

Other: EVAPORATION RATE: NOT ESTABLISHED

X. STABILITY AND REACTIVITY

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Hazardous Decomposition Products: CARBON OXIDES, LEAD OXIDES, MANGANESE

Incompatible Products: REDUCING AGENTS, REACTIVE ORGANICS

Conditions To Avoid: NONE

XI. TOXICOLOGICAL INFORMATION

XII. ECOLOGICAL INFORMATION

XIII. DISPOSAL CONSIDERATIONS

Disposal Method:

FOLLOW LOCAL, STATE AND FEDERAL GUIDELINES.
MATERIAL AND CLEANING SOLUTION IS NOT CONSIDERED HAZARDOUS.

XIV. TRANSPORT INFORMATION

XV. REGULATORY INFORMATION

XVI. OTHER INFORMATION

WARRANTY INFORMATION

THIS INFORMATION IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION.
NO WARRANTY, EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND
SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD
REVIEW THESE RECOMMENDATIONS IN THE SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE
WHETHER
THEY ARE APPROPRIATE.